

## TECHNICAL DATA SHEET

**Code item:** 20

**Description:** tap.

**Material:** PP (polypropylene)

**Gasket:** rubber or silicone suitable for food contact.

**Food fitness:** suitable for food contact.

**Note:** Wash thoroughly before use.



Item	Diameter	Connection diameter (mm)	Weight kg
20/1-BIL	1 inch	32 (external)	0,3
20/1/4-BIL	1/4 inch	31 (internal)	0,02
20/3/4-BIL	3/4 inch	26 (external)	0,03

### Characteristics of the material:

Melt Flow Index (2,16 kg at 190°C)	g/10'	10
Density (at 23°C)	g/cm³	0,905
Max working temperature	°C	+ 100
Min working temperature	°C	- 20
Breaking load	N/mm²	30
Elongation at break	%	>50
Impact resistance at 0°C	Kj/mm²	20
Hardness (Shore D)	N/mm²	75
Global migration	mg/dm²	< 2

### MOBIL PLASTIC S.p.A.

Via Robbio, 31 - 27030 Confienza (PV) - ITALIA

Tel. +39 0384 674692 (3 linee r.a.) - Fax +39 0384 674696

Web site: <http://www.mobilplastic.it> e-mail: [info@mobilplastic.it](mailto:info@mobilplastic.it)

Reg. Impr. Pavia, P. IVA e C. F. IT 00186030185

CAPITALE SOCIALE € 500.000,00 I.V. - R.E.A. PV n° 125850